



mägno Teknik











MTCMC1005 Series Common Mode Choke

Features

- Product weight: 10 g (ref.)Moisture sensitivity Level 1
- Operating Voltage: 250 Vac
- Enameled copper wire: H class
- Ferrite Toroidal core construction
- Inductance Test Condition:: 10KHz / 0.1V
- Rated Current based on temp. rise 40 max.
- Hi-Pot Test N1 to N2: AC 1.5 KV / 50Hz / 5mA /
- 2 Sec
- Operating Temperature: -25°C to +125°C

Product Image




*Displayed image is only for reference purpose, original product may vary.


Applications

- BLDC
- EMI Filter
- LED Drivers
- Control Panels
- DC-DC Converters
- Switching Power Supplies


Dimensions




Front View



Side View



Bottom View



		C (mm)				
15.00 Max	7.50 Ref	17.50 Max	2.50 Ref	10.00 Ref	4.50 Ref	0.70 Ref

Electrical Specifications

Part Number	Inductance, L (mH)	DCR (Ω)	Rated Current (A)	
MTCMC1005102	1	0.04	2.1	
MTCMC1005402	4	0.13	1.6	
MTCMC1005502	5	0.21	1.1	
MTCMC1005103	10	0.34	0.8	
MTCMC1005203	20	0.99	0.55	
MTCMC1005393	39	2.9	0.32	

NOTE:

This land pattern is for reference purposes only. Consult your manufacturing group to ensure your company's manufacturing guidelines are met. Magno Teknik owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of Magno Teknik's product/patent coverage may be accessed at www.magnoteknik.com. Magno Teknik reserves the right to make changes without further notice to any products herein. Magno Teknik makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Magno Teknik assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using Magno Teknik products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by Magno Teknik. "Typical" parameters which may be provided in Magno Teknik data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Magno Teknik does not convey any license under its patent rights nor the rights of others. Magno Teknik products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use Magno Teknik products for any such unintended or unauthorized application, Buyer shall indemnify and hold Magno Teknik and its officers, employees, subsidiaries, affiliates, and eservifue use, even if such claim alleges that Magno Teknik was negligent reg