

mägno Teknik



MTCMC12116501 Common Mode Choke











Features

- Suitable for wave soldering
- Operating Voltage: 250 Vac
- High common mode impedance
- Hi-Pot: N1/N2- AC 600 V (60 Hz 1mA 3 Sec) N1~C/N2~C- AC 600 V (60 Hz 1mA 3 Sec)
- Operating temperature: -25 °C to +105 °C

Product Image





Displayed image is only for reference purpose, original product may vary.


Applications

- Main filter
- White Goods
- EMI Suppression
- Power Supplies (SMPS)
- Suppression of common mode noise

Dimensions







Inductor Structure

No	of	Turns	10	5T

A (mm)	B (mm)	C (mm)	D (mm)	D1 (mm)	D2 (mm)	L (mm)
12 Max.	11 Max.	6 Max.	0.5 ± 0.05	4.0 Ref.	4.5 Ref.	5.0 Min.

Test Method

Test Conditions: 1KHz / 0.3 V

■ Test Equipment: Chroma - 3302 16502

Electrical Characteristics

Part Number	Inductance	Tolerance	DCR	Rated Current
Part Number	N1/N2	N1/N2	mΩ	mA
MTCMC12116501	500μΗ	400μH (Min.)	16 (Max.)	3000 (Typ.)

NOTE:

This land pattern is for reference purposes only. Consult your manufacturing group to ensure your company's manufacturing guidelines are met. Magno Teknik owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of Magno Teknik products for any product for circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using Magno Teknik products, including complication or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using Magno Teknik products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by Magno Teknik. "Typical" parameters which may be provided in Magno Teknik data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use Magno Teknik products for any such unintended or unauthorized application, Buyer shall indemnify and hold Magno Teknik and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Magno Teknik was negligent regarding the design or manufacture of the part. Magno Teknik is an Equal

MAGNO TEKNIK s.r.o. Email: sales@magnoteknik.com | www.magnoteknik.com