

mägno Teknik











MTSFB0805 Series SMD Ferrite Bead - 0805 Size

Features

- Temperature stability
- Low DCR, small package
- SPQ = 4000 pieces/Reel
- Suitable for re-flow soldering
- High current handling capacity
- Nickel barrier terminations provide excellent solder heat resistance
- Operating Temperature: -55 °C ~ +125 °C

Product Image




*Displayed image is only for reference purpose, original product may vary.

Applications

- LED Drivers
- Energy Meter
- Controller Cards
- IOT Applications
- Noise Attenuation
- DC-DC Converters
- Embedded systems
- Power Supplies (SMPS)

Dimensions



A (mm)	B (mm)	C (mm)	D (mm)
2.0 ± 0.2	1.2 ± 0.2	0.9 ± 0.2	0.5 ± 0.2

Electrical Specifications

Part Number	Impedance (Z) at 100 MHz (Ω)	DC Resistance (Ω)	Rated Current (A)
MTSFB0805110C	11	0.01	6
MTSFB0805170C	17	0.01	6
MTSFB0805220C	22	0.01	6
MTSFB0805300C	30	0.03	4
MTSFB0805600C	60	0.05	3
MTSFB0805800C	80	0.06	3
MTSFB0805121C	120	0.08	2.5
MTSFB0805221C	220	0.1	2
MTSFB0805301C	300	0.1	2
MTSFB0805471C	470	0.2	2
MTSFB0805561C	560	0.3	2
MTSFB0805601C	600	0.3	2
MTSFB0805102C	1000	0.3	1.5
MTSFB0805152C	1500	0.3	1
MTSFB0805202C	2000	0.5	0.3
MTSFB0805222C	2200	0.55	0.2
MTSFB0805272C	2700	0.6	0.2

NOTE:

This land pattern is for reference purposes only. Consult your manufacturing group to ensure your company's manufacturing guidelines are met. Magno Teknik owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of Magno Teknik's product/patent coverage may be accessed at www.magnoteknik.com. Magno Teknik reserves the right to make changes without further notice to any products herein. Magno Teknik makes no warranty, representation or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using Magno Teknik products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by Magno Teknik. "Typical" parameters which may be provided in Magno Teknik data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Magno Teknik does not convey my license under its patent rights nor the rights of others. Magno Teknik products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use Magno Teknik products for any such unintended or unauthorized application, Buyer shall indemnify and hold Magno Teknik and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use or u

MAGNO TEKNIK s.r.o. Email: sales@magnoteknik.com | www.magnoteknik.com